

LIQUID EJECTING RECORDING HEAD  
AND LIQUID EJECTING RECORDING APPARATUS

FIELD OF THE INVENTION AND RELATED ART

5           The present invention relates to a liquid  
ejecting recording head and a liquid ejection  
recording apparatus, which apply various liquids, for  
example, inks different in color, to recording media,  
for example, a sheet of paper. In particular, it  
10       relates to a liquid ejecting recording head and a  
liquid ejecting recording apparatus, which are  
employed by a bidirectional printing apparatus, that  
is, a printing apparatus capable of recording in  
either the forward or backward direction by moving a  
15       recording head in a manner to scan a piece of  
recording medium.

          In the field of a printing apparatus, in  
particular, an ink jet type printing apparatus,  
improvement in recording speed in color mode is an  
20       essential theme. As means for improving recording  
speed, increasing the frequency with which a recording  
head is driven, and bidirectional printing, are  
generally considered, in addition to lengthening a  
recording head. In bidirectional printing, the energy  
25       necessary for printing is virtually uniformly  
distributed throughout the time spent for an actual  
printing process. Thus, bidirectional printing is

002227 1 124460

However, bidirectional printing suffers from an inherent problem. That is, it is liable to produce

5 color anomaly in the form of stripes. This is due to  
the fact that in a printing apparatus of a  
bidirectional printing type, the order in which  
various color inks are applied when the printing head  
is moved in one direction in the primary scanning  
10 direction is different from the order in which various  
color inks are applied when it is moved in the other  
direction in the primary scanning direction;  
admittedly the extent of the color anomaly is related  
to printing head configuration. Since this problem is  
caused by the order in which inks are applied,  
15 overlapping of dots different in color results in a  
certain amount of color aberration, no matter how  
small the amount of the overlapping.

Laid-Open Japanese Patent Application 58-  
20 208,143/1983 discloses a liquid ejecting recording  
head structure for solving the above described  
problem. According to this patent application,  
nozzles for different color inks are aligned in the  
secondary scanning direction.

25                   Laid-Open Japanese Patent Application 58-  
179,653/1983 discloses a liquid ejection recording  
head structure which comprises a nozzle set for the

15 Further, Japanese Laid-Open Patent  
Application 58-215,352/1983 discloses a recording head  
structure, according to which a recording cartridge  
comprises a group of recording heads, which are  
different in the color of the inks they eject, and are  
20 staggered relative to each other in the direction in  
which recording medium is conveyed. This structural  
arrangement makes it possible to increase the ejection  
orifice pitch of each recording head relative to a  
desired image resolution. Therefore, it is superior  
25 in that a high resolution image can be easily formed  
with the use of this structural arrangement.

However, a structure such as the one

disclosed in Japanese Laid-Open Patent Application 1-  
208,143/1989 makes a recording head relatively long  
compared to the size of the recording area covered by  
each color, creating a problem in that this structure  
5 makes apparatus dimension relatively large in terms of  
the secondary scanning direction.

On the other hand, a structure such as the  
one disclosed in Japanese Laid-Open Patent  
Applications 58-208143/1983 and 58-215352/1983  
10 increases head size in the primary scanning direction,  
creating a problem in that this structure makes  
apparatus dimension increases in terms of the primary  
scanning direction. Increase of recording head size  
in the primary scanning direction results in increase  
15 in scanning time, being undesirable from the  
standpoint of high speed recording.

A structure such as the one disclosed in  
Japanese Laid-Open Patent Application 58-215,352/1983  
causes head misalignment relative to each other when a  
20 plurality of heads are combined to form a recording  
head portion; in other words, it is liable to cause  
production errors. In particular, in the case of a  
recording head portion which ejects four different  
color inks, that is, Y, M, C, and Bk inks, the  
25 recording heads must be fixed in the order of Y-Bk-M-  
C-C-M-Bk-Y, with each recording head being displaced  
from the adjacent recording head by half a nozzle

pitch. Assembling this type of recording head portion is liable to make the structure for aligning the plurality of recording heads complicated, as well as to increase the size of such a structure.

5

SUMMARY OF THE INVENTION

One of the primary objects of the present invention is to solve the various problems of a recording head capable of bidirectionally recording, for example, a problem that employment of such a recording head is liable to make a recording apparatus large, a problem that such a recording head is difficult to uniformly mass-produce, and the like problems, so that it becomes possible to provide a superior compact liquid ejecting recording head and a superior compact liquid ejecting recording apparatus, that is, a compact liquid ejecting recording head and a compact recording apparatus which are capable of producing a high resolution image of high quality in spite of their compact size.

Another object of the present invention is to provide a liquid ejecting recording head which records by ejecting a first liquid, and a second liquid different from the first liquid, from a group of ejection orifices and another group of ejection orifices, respectively, while being bidirectionally moved along the surface of recording medium, and is

002227 1E424650

characterized in that the ejection orifices are  
divided into first and second groups in which the  
ejection-orifices are aligned at a predetermined  
pitch, in first and second columns, and third and  
5 fourth columns, respectively, in the direction  
different from the direction in which the recording  
head is bidirectionally moved in the scanning manner,  
as well as in a plurality of rows, in the same  
direction as the direction in which the recording head  
10 is bidirectionally moved in the scanning manner; the  
first and second groups are placed adjacent to each  
other in such a manner that the first and third  
columns of ejection orifices in the first and second  
groups, respectively, are placed adjacent to each  
15 other; the first and second columns of ejection  
orifices, that is, the two columns of ejection  
orifices in the first group of ejection orifices,  
eject the first and second liquids, respectively, and  
the third and fourth ejection orifice columns, that  
20 is, the two columns of ejection orifices in the second  
group of ejection orifices, eject the first and second  
liquids, respectively; and the first and second groups  
of ejection orifices are staggered from each other in  
the column direction so that the first and second  
25 groups of ejection orifices compensate for each other  
in terms of the aforementioned primary scanning  
direction.

002221 "T424250

000000 " 132243 097424260

According to the above described liquid  
ejecting head, a color image with a desired high  
resolution can be produced simply by fixing the  
positional relationship between the first and second  
5 groups of ejection orifice columns. Further, the  
first and second groups of ejection orifice columns  
are disposed adjacent to each other in such a manner  
that the third and first ejection orifice columns in  
the first and second groups of ejection orifice  
10 columns, respectively, which eject the same liquid, or  
the first liquid, are placed adjacent to each other.  
Therefore, it is possible to make the third and first  
ejection orifice columns in the first and second  
groups of ejection orifice columns, respectively,  
15 share the same liquid supplying path, allowing  
recording head size to be reduced in both the primary  
and secondary scanning direction of the recording  
head.

As preferable additional structures to the  
20 above described structure arrangement, the following  
structures, the details of which will be described  
later, may be listed. Although these additional  
structures are capable of independently displaying  
remarkable effects, a structure created by combining a  
25 plurality of combinable structures among the  
aforementioned additional structures will be superior  
in terms of the object of the present invention,

because of synergistic effects from the combination.

The above described liquid ejecting head may be provided with a common liquid chamber from which the aforementioned first liquid is supplied to both the third ejection orifice column of the first ejection orifice group, and the first ejection orifice columns of the second ejection orifice group.

The ejection orifice columns in the first and second ejection orifice groups do not need to be limited to those which eject either the first or second liquid. In other words, the first and second ejection orifice groups may comprise an ejection orifice column for ejecting a third liquid different from both the first and second liquids. In particular, when yellow, magenta, and cyan inks are used, the first liquid is desired to be yellow ink.

In order to achieve a higher level of image quality while bidirectionally printing, the ejection orifice columns in the first and second ejection orifice groups are desired to be arranged in such a manner that the two ejection orifice columns which are identical in the liquid they eject are virtually symmetrically disposed with respect to the third ejection orifice column of the first ejection orifice group (or first ejection orifice column of the second ejection orifice group).

The ejection orifice column for ejecting,



for example, black ink, may be separately disposed from the first and second groups of ejection orifices.

The first and second groups of ejection orifices may be integrally placed on a single orifice plate. Also, groups of energy transducing elements for ejecting liquid from corresponding ejection orifice groups may also be placed on a single substrate. Integrating the components and portions of a recording head as described above eliminates the need for aligning the ejection orifice groups relative to each other, making it possible to easily provide a more precise recording head.

As the material for the substrate on which the groups of energy transducing elements are disposed, silicon is desirable. When forming the through holes through which liquid is supplied, by anisotropic etching, the crystal face orientation of silicon is desired to be  $\langle 100 \rangle$  or  $\langle 110 \rangle$ . The orifice plate material is desired to be photosensitive epoxy resin so that the aforementioned groups of ejection orifices can be easily formed in highly precise patterns of columns and rows.

Another object of the present invention is to  
25 provide a liquid ejecting recording head which records  
by ejecting a first liquid, and a second liquid  
different from the first liquid, from one group of

002227 "F424260

ejection orifices and another group of ejection orifices, respectively, while being bidirectionally moved along the surface of recording medium, and is characterized in that it comprises an orifice plate provided with a plurality of ejection orifices aligned in a plurality of columns at a predetermined pitch in the direction different from the aforementioned primary scanning direction, and a substrate on which not only energy transducing elements for ejecting liquid are disposed in alignment with the ejection orifices of the orifice plate, but also liquid supplying paths for supplying the columns of ejection orifices of the orifice plate, and a driver circuit for driving the energy transducing elements, are disposed; the ejection orifices of the orifice plate are aligned in four columns in the direction different from the primary scanning direction, in the order of the first column which ejects the second liquid, the second column which ejects the first liquid, the third column which ejects the first liquid, and the fourth column which ejects the second liquid, in terms of the primary direction; and a single liquid supply path for supplying the first liquid supplies both the second and third columns of ejection orifices with the first liquid.

According to the above described recording head, it is unnecessary to adjust the positional

relationship between the two groups of ejection  
orifices, making it easier to provide a highly precise  
head. Further, the liquid supplying path for one  
column of ejection orifices, and the liquid supplying  
5 path for another column of ejection orifices adjacent  
to the first column of ejection orifices can be  
integrated into a single liquid supplying path, making  
it possible to reduce recording head size in both the  
primary and secondary scanning directions. In  
10 addition, it is possible to place the aforementioned  
driver circuit in the area in which no liquid  
supplying holes are present.

In this specification, "recording medium"  
means not only such paper that is used by an ordinary  
15 printing apparatus, but also fabric, plastic film,  
metallic plate, and the like, in other words, a wide  
range of media capable of taking ink.

"Ink" means such liquid that is used to form  
an image, an abstract pattern, and the like, or to  
20 process printing medium, by being applied to printing  
medium.

"Pixel region" means a smallest unit of  
region to which a single or a plurality of droplets of  
ink to exhibit a primary or secondary color. Not only  
25 does it include a standard pixel, but also a super  
pixel and a sub-pixel. The number of scanning runs  
for completing a single pixel does not need to be one;

Further, "process color" includes secondary color, that is, color exhibited by mixing three or more inks on printing medium.

5 As described above, according to the present invention, a color image with a desired high level of resolution can be produced simply by adjusting the positional relationship between the first and second groups of ejection orifices. Further, the first and second groups of ejection orifices can be placed adjacent to each other in such a manner that the ejection orifice column in the first ejection orifice group, which ejects the first liquid, and the ejection orifice column in the second ejection orifice group, which also eject the first liquid, are placed adjacent to each other, making it possible to make these two columns of ejection orifices share the same liquid path. Consequently, recording head size can be reduced in both the primary and secondary scanning directions, and it becomes easy to print at high speed, without causing unevenness in color, even in bidirectional printing.

These and other objects, features, and advantages of the present invention will become more apparent upon consideration of the following description of the preferred embodiments of the present invention, taken in conjunction with the

accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

5 Figure 1 is a schematic drawing which depicts the essential portion of the recording head in the first embodiment of the present invention.

10 Figure 2 is a schematic drawing which depicts an example of a recording head cartridge which holds the recording head in the first embodiment of the present invention.

Figure 3 is a schematic drawing which depicts the essential portion of the recording head in the second embodiment of the present invention.

15 Figure 4 is a schematic drawing which depicts an example of a recording head cartridge which holds the recording head in the second embodiment of the present invention.

20 Figure 5 is a schematic drawing which depicts the essential portion of the recording head in the third embodiment of the present invention.

Figure 6 is a schematic drawing which depicts the essential portion of the recording head in the fourth embodiment of the present invention.

25 Figure 7 is a schematic drawing which depicts an example of the relationship between the ejection nozzle position and pixel structure in an embodiment of the present invention.

002221 13200  
F424250

Figure 8 is a schematic drawing which shows the image formation sequence through which an image is formed by a recording head in accordance with the present invention, while which prints bidirectionally.

5           Figure 9 is an enlarged drawing which shows the extent of dot expansion relative to a single pixel in Figure 7.

10           Figure 10 is a schematic drawing of an example of a recording apparatus in which a liquid ejecting recording head in accordance with the present invention can be mounted.

#### DESCRIPTION OF THE PREFERRED EMBODIMENTS

15           Hereinafter, embodiments of the present invention will be described in detail with reference to the appended drawings.

##### Embodiment 1

20           Figure 1 is a schematic drawing which shows the essential portion of the recording head in the first embodiment of the present invention. Figure 1(a) is a top view, and Figure 1(b) is a schematic drawing for describing the positioning of the ejection orifices. Figure 1(c) is a sectional drawing. As is shown in Figure 1(c), a recording head 300 in this  
25           embodiment comprises a substrate 7 inclusive of exothermal elements 5 as energy transducers, and an orifice plate 6 which has ejection orifices 1.

00000 " 1234567890

20

25

and liquid paths 10, which were formed in alignment with the aforementioned exothermic elements, with the use of a process such as the one recorded in Japanese Laid-Open Patent Application 62-264,957/1987. More specifically, as is described in Japanese Laid-Open Patent Application 9-11,479/1997, after silicon oxide film or silicon nitride film was formed on the silicon substrate, the orifice plate with the through holes and liquid paths was formed, and the silicon oxide film or silicon nitride film was removed from the regions correspondent to the ink supplying holes, with the use of the aforementioned anisotropic etching. This method is desirable because it makes it possible to produce such an ink jet head that is inexpensive and yet highly precise.

The recording head 300 having the above described substrate 7 and orifice plate 6 records by ejecting liquid, for example, ink, from the ejection orifices 1 with the use of the pressure from the bubbles generated through the film boiling caused by the thermal energy applied by the electrothermal transducers 5. As shown in Figure 2(a), the recording head 300 is fixed to an ink path member 12 connected to the aforementioned ink supplying holes, causing the contact pad to be placed in contact with the wiring plate 13. As the contact pad is placed in contact with the wiring plate 13, an electrical contact



portion 11 of this wiring plate is placed in contact with the electrical contact portion of a recording apparatus which will be described later. As a result, the recording head 300 can receive driving signals or the like from the recording apparatus. Figure 2(b) is a perspective view which shows an example of the recording head cartridge 100 equipped with the recording head 300 in accordance with the present invention. As shown in Figure 2(b), this recording head cartridge is provided with an ink container holder 150 in which ink containers 200 (200Y, 200M, and 200C) for supplying inks to the aforementioned ink path member 12 are held.

Further, the recording head in this embodiment is provided with a plurality of ejection orifices 1 which are arranged with a predetermined pitch, forming plural columns 21 - 23, and 31 - 33, of ejection orifices, which are virtually parallel to each other. In Figure 1(a), among the ejection orifice columns 21 - 23, the i-th ejection orifice in each column of ejection orifices, counting from the top side of the drawing, aligns with the i-th ejection orifices in the other columns of ejection orifices, in the direction indicated in Figure 1(a). In other words, the ejection orifice columns 21 - 23 in this embodiment are arranged so that the direction in which the i-th ejection orifice in each column of ejection

orifices, counting from the top side of the drawing,  
is aligned with the i-th ejection orifices in the  
other columns of ejection orifices, coincides with the  
direction in which the recording head mounted in the  
5 recording apparatus, which will be described later, is  
moved in a manner of scanning. The ejection orifice  
columns 21 - 23 makes up a first ejection orifice  
group 20. The ejection orifice columns 31 - 33 are  
arranged in the same manner as the ejection orifice  
10 columns 21 - 23, and makes up a second ejection  
orifice group 30, which is disposed adjacent to the  
first ejection orifice group 20.

In this embodiment, among the six ejection  
orifice columns constituting two groups of ejection  
15 orifices, the outermost ejection column of each group,  
that is, the ejection orifice columns 23 and 33, are  
assigned to eject cyan (C), and ejection orifice  
columns 22 and 33 are assigned to eject magenta (M).  
The innermost ejection orifice columns 21 and 33,  
20 which are adjacent to each other, are assigned to  
eject yellow (Y). Thus, yellow ink is supplied to the  
aforementioned ink supplying hole 2a (ink supplying  
hole located in the center) from the aforementioned  
ink container 200, and magenta ink is supplied to the  
25 ink supplying holes 2 adjacent to the ink supplying  
hole 2a, from the ink container 200M. Cyan ink is  
supplied to the outermost ink supplying holes 2 from

the ink container 200C. As is evident from the above description, the ink supplying hole 2a in the center supplies two ejection orifice columns 21 and 31 with liquid, and functions, along with the liquid path 10a, as a common liquid chamber for the two ejection orifice columns 21 and 31.

As described above, in this embodiment, the ejection orifices aligned in a plurality of columns, and the plurality of ejection orifice columns are divided into two groups which are identical to each other in the number of inks and colors of inks. Further, the ejection orifice columns and the driving circuits therefor are virtually symmetrically disposed with respect to the approximate center line which divides the ejection orifice columns into the first and second groups. With this arrangement, the through holes as the ink supplying holes 2 and 2a, driver circuits, exothermic elements, and the like, can be positioned on the substrate, with even intervals and a high level of spacial efficiency. In this embodiment, the size of each exothermic element 5 is 30  $\mu$ m x 30  $\mu$ m, and the widths of the ejection orifice, driver circuit, and wiring (a in Figure 1(a)) are 1.2 mm. The width of the top opening (b in Figure 1(c)) of the ink supplying hole 2 is 0.2 mm. Thus, the substrate size may be 8.2 mm (= 2 x 6 + 0.2 x 5). Being able to reduce the substrate size as described above is

advantageous in that it makes it possible to reduce the capacity of the memory for holding the transfer data from a recording head, in proportion to the substrate size.

5 In addition, in this embodiment, as is  
evident from Figures 1(a) and 1(b), the first ejection  
orifice column group 20 and second ejection orifice  
column group 30 are staggered in the ejection orifice  
column direction so that the ejection orifices of the  
10 ejection orifice columns 21 - 23 which make up the  
first ejection orifice column group 20, and the  
ejection orifices of the ejection orifice columns  
which make up the ejection orifice column group 30,  
compensate among themselves in terms of the  
15 aforementioned scanning direction. Further, as is  
evident from Figure 1(b), each of the ejection orifice  
columns of the first and second ejection orifice  
column groups has 128 ejection orifices which are  
aligned with an interval (pitch) of approximately 40  
20  $\mu\text{m}$ :  $t_1 = t_2 \doteq 40 \mu (1/600 \text{ inch})$ . The ejection orifice  
column 21 is staggered from the ejection orifice  
column 31 in the secondary scanning direction of the  
recording head (in this embodiment, this direction  
coincides with the direction of each ejection orifice  
25 column) by exactly 1/2 pitch ( $t_3 = 1/2 t_1 \doteq 20 \mu\text{m}$ ).

At this point, an example of the recording method by this recording head will be described with

In this embodiment, recording is effected by ejecting approximately 8 pls of ink from each nozzle. The recording apparatus (Figure 10) in which the recording head in this embodiment is mounted is capable of operating in two different modes, that is, high speed mode and high resolution mode, to form an image.

Figures 7 and 8 are schematic drawings which depict an image forming operation in the aforementioned high speed mode. In this high speed mode, in order to reduce the time used for image processing and data transfer, two liquid droplets are deposited in each pixel in such a manner that the location on which one liquid droplet lands differs from the location on which the other liquid droplet lands. Incidentally, the pixel density in this embodiment is 600 pixels per inch in both the primary and secondary scanning direction. Figure 7 shows a case in which cyan and yellow dots were recorded on the same spot. A pixel (p) 230 formed by the primary scanning lines (rasters)  $R_{11}$  and  $R_{12}$  is recorded as a pair of dots, that is, a dot deposited in a dot position 231 and a dot deposited in a dot position 232. Here, the dot positions are diagonally arranged; the dot position ( $d_1$ ) 231 is at the top left corner of the pixel, and the dot position ( $d_2$ ) 232 is at the

bottom left corner of the pixel. In this drawing, the dot in the dot position  $d_1$  and the dot in the dot position  $d_2$  do not overlap with each other. In reality, however, it is common that the two dots partially overlap with each other as shown in Figure 9 (hatched area).

Further, in this embodiment, in which a pixel  $p$  is formed by two rasters ( $R_{(n-1)1}$ ,  $R_{(n-1)2}$ ), a nozzle pitch  $\underline{12}$  is approximately  $40\text{ }\mu\text{m}$  ( $1/600$  inch). Since the first ejection orifice column group 20 is staggered by half a pitch from the second ejection orifice column group 30 in the secondary scanning direction, an interval  $\underline{11}$  between the adjacent two rasters is approximately  $20\text{ }\mu\text{m}$  ( $1/1200$  inch).

When a printing operation is carried out using only a single primary color, for example, magenta, an image is formed by ejecting a single droplet of magenta ink onto the dot position  $d_1$  of each pixel  $p$  from correspondent ejection orifice of the ejection orifice column 22 (hereinafter,  $M1$ ), and another single droplet of magenta ink onto the dot position  $d_2$  of the same pixel  $p$  from the correspondent ejection orifice of the ejection orifice column 32 (hereinafter,  $M2$ ), regardless of the scanning direction (in this case, two dots are the same in color, and therefore, the order in which two ink droplets are ejected does not affect the color

exhibited by a combination of the two ink droplets).

However, when a printing operation is carried out in a secondary color, for example, green, as shown in Figure 7, an image is formed by ejecting onto each pixel p a single droplet of liquid from the correspondent ejection orifice of the ejection orifice column 23 (hereinafter C1), a single droplet of liquid from the correspondent ejection orifice of the ejection orifice column 21 (hereinafter, Y1), a single droplet of liquid from the correspondent ejection orifice of the ejection orifice column 31 (hereinafter, Y2), and a single droplet of liquid from the correspondent ejection orifice of the ejection orifice column 33 (hereinafter, C2).

When printing in the forward direction, the order in which the ejection orifice columns pass a predetermined pixel p on a piece of recording medium is  $C1 \rightarrow Y1 \rightarrow Y2 \rightarrow C2$ . Therefore, the liquid droplets land on the pixel p in the order shown in Figures 8(a)  $\rightarrow$  8(d). In the dot position  $d_1$  of the pixel p, the liquid droplets land in the order of  $C \rightarrow Y$ , and therefore, cyan color exhibited by the liquid droplet which lands first become dominant. On the other hand, in the dot position  $d_2$ , the liquid droplets land in the order of  $Y \rightarrow C$ , and therefore, yellow color exhibited by the liquid droplet which lands first becomes dominant.

५

15

25



5 As described above, the liquid depositing order is symmetrical, in other words, the order in which the inks are adhered is the same as in the forward direction. Therefore, the pixels appears uniformly green. In other words, even when printing is  
10 bidirectionally carried out, a printed image does not appear uneven in color.

Next, a high resolution mode will be described. In this mode, the resolution in the primary scanning direction is 600 pixels per inch, and the resolution in the secondary scanning direction is 1,200 pixels per inch. In monochromatic printing (printing in C, M, or Y), a single droplet of liquid is ejected per pixel. In this case, the pixels are divided into a group painted by a combination of C1, M1, and Y1, and a group painted by a combination of C2, M2, and Y2, by masking the image formation area. With this arrangement, the pixel density in the secondary scanning direction can be made to be 1,200 per inch, even though the nozzle density in each ejection orifice column is 600 per inch. Consequently, a highly precise image can be easily formed. Also in this high resolution mode, when

printing in green, for example, pixels coated by a combination of C1 and Y1 (since liquids are adhered to recording medium in the order of C and Y, cyan becomes dominant) and pixels coated by a combination of C2 and Y2 (since liquids are adhered to recording medium in the order of Y and C, yellow becomes dominant), are present in mixture; pixels different in color are present in mixture. However, unevenness in color can be reduced to a hardly detectable level by evenly distributing the pixels different in color by proper masking.

The above described recording method is one of the bidirectional printing methods which can be carried out with the use of a liquid ejecting head in accordance with the present invention. Further, the recording mode used with the image forming method which uses a liquid ejecting head in accordance with the present invention does not need to be limited to the above described two recording modes.

## Embodiment 2

Figures 3 and 4 are drawings which show the recording head in the second embodiment of the present invention, and a recording head cartridge in which this recording head is mounted. In the drawings, the components and portions which are the same in function as those in the first embodiment are given the same referential codes as those in the first embodiment,

and their detailed descriptions will be not be given.

Figure 3 is a schematic drawing which depicts the essential portion of the recording head. Figure 3(a) is a schematic drawing as seen from the top, and

5 Figure 3(b) is a schematic drawing which depicts the positioning of the ejection orifices. Figure 3(c) is a sectional view. Figure 4(a) is a perspective view of the recording head illustrated in Figure 3, which is fixed to an ink path member 12, and Figure 4(b) is  
10 a perspective view of an example of a recording head cartridge 100 equipped with the recording head 300 in accordance with the present invention. Figure 4(c) is a perspective view of the recording head cartridge illustrated in Figure 4(b), and ink containers  
15 removably installable in this recording head cartridge.

Firstly, this embodiment is different from the first embodiment in that a silicon substrate with a crystal face orientation of  $\langle 110 \rangle$  is used. In this  
20 embodiment, when forming ink supplying holes 2 and 2a by etching, the etching progresses perpendicularly to the substrate. Therefore, it is easy to form the ink supplying holes 2 and 2a in this embodiment, which are uniform in cross-section perpendicular to the  
25 thickness direction of the substrate as shown in Figure 3(c). Thus, the substrate size is determined by the patterns formed on the substrate surface,



ejection orifice columns 21 and 31 do, making it possible to record at a resolution level equivalent to twice the nozzle arrangement density in each ejection orifice column.

5           Also in this embodiment, a printing operation  
can be carried out in the recording modes in the above  
described first embodiment.

### Embodiment 3

Figure 5 is a drawing which shows the recording head in the third embodiment of the present invention. In this drawing, the components and portions which are the same in function as those in the first and second embodiments are given the same referential codes as those in the first and second embodiments, and their detailed descriptions will be not be given. Figure 5 is a schematic drawing which depicts the essential portion of the recording head. Figure 5(a) is a schematic drawing as seen from the top, and Figure 5(b) is a schematic drawing which depicts the positioning of the ejection orifices. Figure 5(c) is a sectional view.

This embodiment is different from the first and second embodiments in that the number of through holes provided in the substrate 7 is three. The ink supplying holes 2b correspondent to the two outermost ejection orifice columns are formed by the edge portions of the substrate 7 and the ink path member

### Embodiment 4

15                In this embodiment, the ejection orifice  
columns 24 and 34 for ejecting black ink (Bk) are  
placed in the first and second ejection orifice column  
groups, respectively.

According to this embodiment, the minimum  
20 requirement for carrying out the recording method for  
reducing the unevenness in color, which was described  
in detail regarding the first embodiment, in a  
bidirectional printing, is that one of each pair of  
ejection orifice columns which deposit liquids in an  
25 overlapping manner and are different in liquid is  
included in the first group of ejection orifices, and  
the other of the pair is included in the second group

of ejection orifices; as long as this requirement is satisfied, the aforementioned effect, that is, reduction in the unevenness in color, can be realized. However, in order to produce an image with far less unevenness in color, it is desired that one of each pair of ejection orifice columns which eject liquids in an overlapping manner, and the other of the pair, are symmetrically arranged as in each of the preceding embodiments described above.

10           In each of the preceding embodiments described above, the present invention was described with reference to cyan, magenta, and yellow inks, which are most widely used in the field of ink jet recording, as the liquids deposited in an overlapping manner. However, cyan, magenta, and yellow inks, which are less in saturation, may be included among the liquids to be deposited in an overlapping manner. Further, the aforementioned of inks of primary color, which are deposited in combination to exhibit blue, red, and the like colors may be different from those used in this embodiment. In other words, the combination of liquids described, in this specification, different in "type" may a combination of inks different in color, as well as a combination of inks which are the same in color but different in density.

          In the preceding embodiments of the present

invention, the first and second columns of ejection orifices were placed on the same orifice plate, or the energy transducing elements for ejecting liquid from the ejection orifices in the first column, and the energy transducing elements for ejecting liquid from the ejection orifices in the second column, were placed on the same orifice plate. However, the first and second columns of ejection orifices may be placed on different recording heads which are combined later. With this arrangement, all that is necessary is to adjust the position of the two heads relative to each other to meet the requirements of the present invention. Nevertheless, the structures in the preceding embodiments are preferable in that they eliminate the need for aligning the ejection orifice columns in two different recording heads.

#### Miscellany

Lastly, a liquid ejecting recording apparatus in which the above described recording heads or recording heads in the preceding embodiments of the present invention can be installed will be described. Figure 10 is a schematic drawing which depicts an example of a recording apparatus in which a liquid ejecting recording head in accordance with the present invention is installable.

In Figure 10, a head cartridge 100, which is removably installable in the recording apparatus, is



5

10

15

20

25

As a pickup roller 131 is rotated by a sheet feeder motor 135 through a gear train, recording media

5  
10  
15  
20

25

5

10

15

20